## NSN 5905-01-309-4767

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-309-4767 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** 5.0 millimeters **Body Diameter:** 7.3 millimeters **Body Length:** 7.0 millimeters **Actuator Type:** Flush drive with slot-hole **Center To Center Distance Between Terminals:** 5.0 millimeters **Fragility Factor:** Moderately rugged **End Application:** 6625-01-131-6974 meter, selective level **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 5.0 kilohms single section **Center To Center Distance Between Center Terminal And Outside Terminal:** 2.5 millimeters Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 120.0 single section **Power Dissipation Rating Per Section In Watts:** 0.5 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 pin Shelf Life:

N/a

## NSN 5905-01-309-4767

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



		• -						
	In		Of	RЛ	മാ	CI	ır	Δ.
L	,,,			IVI	ca			

--

Demilitarization:

No

Fiig:

A002a0