Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-309-4768

Section	Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

- **Terminal Length:**
- 4.0 millimeters
- **Body Length:**

8.0 millimeters

Body Width:

7.4 millimeters

Body Height:

9.0 millimeters

Actuator Type:

Flush drive with slot-hole

Center To Center Distance Between Terminals:

5.0 millimeters

Fragility Factor:

Moderately rugged

End Application:

6625-01-131-6974 meter, selective level

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

2.5 millimeters

Electrical Resistance Per Section:

20.0 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

2.5 millimeters

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0