Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-309-8034

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-300.0/+300.0

#### **Electrical Resistance:**

20.000 kilohms

### **Resistance Tolerance In Percent:**

-2.000/+2.000

### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

### **Inclosure Method:**

Encapsulated

### **Terminal Quantity:**

8

### **Terminal Type:**

Pin

## **Reliability Indicator:**

Not established

### Terminal Length:

Between 0.125 inches and 0.150 inches

### **Body Length:**

Between 0.768 inches and 0.798 inches

### **Body Width:**

Between 0.050 inches and 0.103 inches

### **Body Height:**

Between 0.177 inches and 0.197 inches

## Schematic Diagram Designator:

Isolated array

### **Power Dissipation Rating In Watts:**

0.480 total network

#### **End Application:**

Ac-130h a d m

### Identical Value Resistor Quantity:

4 each resistor

# Unpackaged Unit Weight:

1.5 grams

#### Style Designator:

Single inline

### **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Film Fixed Resistor Network - Page 2 of 2



**Specification Data:** 

81349-mil-r-83401/8 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0