Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-310-9593

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

Electrical Resistance:

220.000 ohms

Resistance Tolerance In Percent:

-2.000/+2.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

Inclosure Method:

Encapsulated

Terminal Quantity:

6

Terminal Type:

Pin

Reliability Indicator:

Not established

Terminal Length:

Between 0.125 inches and 0.150 inches

Body Length:

Between 0.568 inches and 0.598 inches

Body Width:

Between 0.050 inches and 0.103 inches

Body Height:

Between 0.177 inches and 0.195 inches

Schematic Diagram Designator:

Ladder network

Power Dissipation Rating In Watts:

0.600 total network

End Application:

1440-01-215-4868 armament subsystem, helicopter, guided missile launcher

Identical Value Resistor Quantity:

5 each resistor

Unpackaged Unit Weight:

1.3 grams

Style Designator:

Single inline

Test Data Document:

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Film Fixed Resistor Network - Page 2 of 2



Specification Data:

81349-mil-r-83401/7 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A001a0