## NSN 5905-01-311-0572

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-311-0572

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -25.0/+25.0  Electrical Resistance: 20.000 kilohms  Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 105.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0  Inclosure Method: Encapsulated  Terminal Quantity: 8  Terminal Type: Pin  Reliability Indicator: Not established  Body Length: Between 0.880 inches and 0.920 inches  Body Width: 0.095 inches  Body Height: Between 0.480 inches and 0.520 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts: 0.400 total network End Application:
Electrical Resistance: 20.000 kilohms Resistance Tolerance In Percent: -0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 105.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Body Length: Between 0.880 inches and 0.920 inches Body Width: 0.095 inches Body Height: Between 0.480 inches and 0.520 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.400 total network
20.000 kilohms  Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 105.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0  Inclosure Method: Encapsulated  Terminal Quantity: 8  Terminal Type: Pin  Reliability Indicator: Not established  Body Length: Between 0.880 inches and 0.920 inches  Body Width: 0.095 inches  Body Height: Between 0.480 inches and 0.520 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts: 0.400 total network
Resistance Tolerance In Percent: -0.100/+0.100  Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0  Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 105.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Encapsulated  Terminal Quantity: 8  Terminal Type: Pin  Reliability Indicator: Not established  Body Length: Between 0.880 inches and 0.920 inches  Body Width: 0.095 inches  Body Height: Between 0.480 inches and 0.520 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts: 0.400 total network
-0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 105.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Body Length: Between 0.880 inches and 0.920 inches Body Width: 0.095 inches Body Height: Between 0.480 inches and 0.520 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.400 total network
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 105.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Body Length: Between 0.880 inches and 0.920 inches Body Width: 0.095 inches Body Height: Between 0.480 inches and 0.520 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.400 total network
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  105.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+70.0  Inclosure Method: Encapsulated  Terminal Quantity: 8  Terminal Type: Pin  Reliability Indicator: Not established  Body Length: Between 0.880 inches and 0.920 inches  Body Width: 0.095 inches  Body Height: Between 0.480 inches and 0.520 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts: 0.400 total network
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  105.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius:  -55.0/+70.0  Inclosure Method:  Encapsulated  Terminal Quantity: 8  Terminal Type: Pin  Reliability Indicator: Not established  Body Length: Between 0.880 inches and 0.920 inches  Body Width: 0.095 inches  Body Height: Between 0.480 inches and 0.520 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts: 0.400 total network
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Body Length: Between 0.880 inches and 0.920 inches Body Width: 0.095 inches Body Height: Between 0.480 inches and 0.520 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.400 total network
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Body Length: Between 0.880 inches and 0.920 inches Body Width: 0.095 inches Body Height: Between 0.480 inches and 0.520 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.400 total network
-55.0/+70.0 Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Body Length: Between 0.880 inches and 0.920 inches Body Width: 0.095 inches Body Height: Between 0.480 inches and 0.520 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.400 total network
Inclosure Method: Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Body Length: Between 0.880 inches and 0.920 inches Body Width: 0.095 inches Body Height: Between 0.480 inches and 0.520 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.400 total network
Encapsulated Terminal Quantity: 8 Terminal Type: Pin Reliability Indicator: Not established Body Length: Between 0.880 inches and 0.920 inches Body Width: 0.095 inches Body Height: Between 0.480 inches and 0.520 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.400 total network
Terminal Quantity: 8  Terminal Type: Pin  Reliability Indicator: Not established  Body Length: Between 0.880 inches and 0.920 inches  Body Width: 0.095 inches  Body Height: Between 0.480 inches and 0.520 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts: 0.400 total network
Terminal Type: Pin  Reliability Indicator: Not established  Body Length: Between 0.880 inches and 0.920 inches  Body Width: 0.095 inches  Body Height: Between 0.480 inches and 0.520 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts: 0.400 total network
Terminal Type: Pin  Reliability Indicator: Not established  Body Length: Between 0.880 inches and 0.920 inches  Body Width: 0.095 inches  Body Height: Between 0.480 inches and 0.520 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts: 0.400 total network
Pin  Reliability Indicator:  Not established  Body Length:  Between 0.880 inches and 0.920 inches  Body Width:  0.095 inches  Body Height:  Between 0.480 inches and 0.520 inches  Schematic Diagram Designator:  Isolated array  Power Dissipation Rating In Watts:  0.400 total network
Reliability Indicator: Not established  Body Length: Between 0.880 inches and 0.920 inches  Body Width: 0.095 inches  Body Height: Between 0.480 inches and 0.520 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts: 0.400 total network
Not established  Body Length: Between 0.880 inches and 0.920 inches  Body Width: 0.095 inches  Body Height: Between 0.480 inches and 0.520 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts: 0.400 total network
Body Length:  Between 0.880 inches and 0.920 inches  Body Width:  0.095 inches  Body Height:  Between 0.480 inches and 0.520 inches  Schematic Diagram Designator:  Isolated array  Power Dissipation Rating In Watts:  0.400 total network
Between 0.880 inches and 0.920 inches  Body Width:  0.095 inches  Body Height:  Between 0.480 inches and 0.520 inches  Schematic Diagram Designator:  Isolated array  Power Dissipation Rating In Watts:  0.400 total network
Body Width:  0.095 inches  Body Height:  Between 0.480 inches and 0.520 inches  Schematic Diagram Designator:  Isolated array  Power Dissipation Rating In Watts:  0.400 total network
0.095 inches  Body Height:  Between 0.480 inches and 0.520 inches  Schematic Diagram Designator:  Isolated array  Power Dissipation Rating In Watts:  0.400 total network
Body Height: Between 0.480 inches and 0.520 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.400 total network
Between 0.480 inches and 0.520 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts:  0.400 total network
Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.400 total network
Isolated array  Power Dissipation Rating In Watts:  0.400 total network
Power Dissipation Rating In Watts: 0.400 total network
Power Dissipation Rating In Watts: 0.400 total network
End Application:
Liiu Application.
1430-01-286-1314 guided missile system
Identical Value Resistor Quantity:
4 each resistor
Style Designator:
Single inline
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5905-01-311-0572

Film Fixed Resistor Network - Page 2 of 2



Fiig:

A001a0