

View Online at <https://aerobasegroup.com/nsn/5905-01-311-3149>

Reliability Indicator:

Not established

Terminal Length:

1.250 inches

Body Length:

Between 0.390 inches and 0.430 inches

Body Outside Diameter:

Between 0.120 inches and 0.160 inches

Terminal Diameter:

Between 0.022 inches and 0.028 inches

Maximum Power Dissipation Rating:

0.50 milliwatts

Ambient Temperature At Full Rated Power:

25.0 degrees celsius

Maximum Operating Temp:

125.0 degrees celsius

Thermal Time Constant In Seconds:

60.0

Power Dissipation Constant In Milliwatts Per Deg Celsius:

5.0

Temperature Points For Resistance Readings At Zero Power:

75.0 degrees celsius 5th resistance-temperature point

Zero Power Resistance At Specificationified Temp:

930.0 ohms 7th resistance-temperature point

Resistance Tolerance At A Specificationified Temperature In Percent:

-5.0/+5.0 all resistance-temperature points

End Application:

Valve, ball

Inclosure Type:

Encapsulated

Cubic Measure:

0.009 cubic inches

Zero Power Resistance:

500.000 ohms

Zero Power Resistance Tolerance In Percent At Reference Temp:

-5.0/+5.0

Style Designator:

Rod

Test Data Document:

81349-mil-t-23648 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 wire lead

Specification Data:

81349-mil-t-23648/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A086a0