## NSN 5905-01-313-3530

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-313-3530
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0
Electrical Resistance:
22.000 kilohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated  Transition I Occupation
Terminal Quantity:
Terminal Type: Pin
Reliability Indicator:  Not established
Terminal Length:
Between 0.125 inches and 0.150 inches
Body Length:
Between 0.568 inches and 0.598 inches
Body Width:
Between 0.050 inches and 0.103 inches
Body Height:
Between 0.177 inches and 0.195 inches
Schematic Diagram Designator:
Ladder network
Power Dissipation Rating In Watts:
0.060 total network
End Application:
6625-01-251-9860 electro, counter
Identical Value Resistor Quantity:
5 each resistor
Unpackaged Unit Weight:
1.3 grams
Style Designator:
Single inline
Test Data Document:
04040 mil 00404 mar Wasting (includes a principal translation baselines and the traffic translation (includes a principal translation)

81349-mil-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5905-01-313-3530

Film Fixed Resistor Network - Page 2 of 2



Specification Data	Spe	ecifica	ition	Data:
--------------------	-----	---------	-------	-------

81349-mil-83401/7 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0