

View Online at <https://aerobasegroup.com/nsn/5905-01-313-7171>

**Temperature Coefficient Of Resistance In Ppm Per Deg Celsius:**

-100.0/+100.0

**Electrical Resistance:**

60.000 kilohms

**Resistance Tolerance In Percent:**

-1.000/+1.000

**Ambient Temperature In Deg Celsius At Full Rated Power:**

70.0

**Ambient Temperature In Deg Celsius At Zero Percent Rated Power:**

125.0

**Tempurature Range Of Tempurature Coefficient In Deg Celsius:**

-55.0/+125.0

**Inclosure Method:**

Encapsulated

**Terminal Quantity:**

16

**Terminal Type:**

Tab, solder lug

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 0.125 inches and 0.150 inches

**Body Length:**

Between 0.784 inches and 0.876 inches

**Body Width:**

Between 0.240 inches and 0.305 inches

**Body Height:**

0.200 inches

**Schematic Diagram Designator:**

Balanced ladder network

**Power Dissipation Rating In Watts:**

1.600 total network

**Terminal Width:**

Between 0.015 inches and 0.022 inches

**End Application:**

5805-01-187-9399 telephone switchboard

**Identical Value Resistor Quantity:**

8 highest resistance value

**Style Designator:**

Dual inline

**Test Data Document:**

28528-1135587 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A001a0