

View Online at <https://aerobasegroup.com/nsn/5905-01-314-5474>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Terminal Length:

Between 0.120 inches and 0.122 inches

First Flat Length:

0.430 inches

Flat Height:

0.094 inches

Body Diameter:

0.490 inches

Shaft Diameter:

Between 0.122 inches and 0.126 inches

Shaft Length:

0.750 inches

Mounting Bushing Length:

Between 0.235 inches and 0.265 inches

Body Length:

0.550 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Nonturn Device Location:

At 1 Oclock and at 7 oclock

Nonturn Device Radius:

0.245 inches

Center To Center Distance Between Terminals:

0.200 inches

Fragility Factor:

Moderately rugged

End Application:

F-4 chassis k

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Locking bushing

Features Provided:

Panel seal and shaft seal

Electrical Resistance Per Section:

10.0 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Power Dissipation Rating Per Section In Watts:

0.25 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0