NSN 5905-01-315-1414

Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-315-1414 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.8740 inches and 1.8750 inches Pilot Length: Between 0.0570 inches and 0.0670 inches **Undercut Diameter:** Between 1.990 inches and 2.005 inches **Undercut Width:** Between 0.0800 inches and 0.0900 inches **Body Diameter:** Between 1.990 inches and 2.005 inches **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** Between 0.594 inches and 0.656 inches **Body Length:** Between 0.569 inches and 0.631 inches **Mounting Lip Diameter:** Between 1.9900 inches and 2.0050 inches **Mounting Lip Depth:** Between 0.0880 inches and 0.0980 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:**

Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0

Maximum Starting Torque:

0.75 inch-ounces

Maximum Running Torque:

0.75 inch-ounces

Shaft End Play:

0.003 inches

Shaft Runout:

0.001 inches

NSN 5905-01-315-1414

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Lateral Runout:
0.003 inches
Pilot Diameter Runout:
0.001 inches
Shaft Radial Play:
0.003 inches
Mechanical Backlash In Deg Angular Rotation:
0.1
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
350.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-500.0/+500.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5905-01-315-1414

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0