Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-315-8092

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0/+100.0

**Electrical Resistance:** 

1.620 kilohms

**Resistance Tolerance In Percent:** 

-1.000/+1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

**Inclosure Method:** 

Encapsulated

Terminal Quantity:

16

**Terminal Type:** 

Tab, solder lug

Reliability Indicator:

Not established

Terminal Length:

Between 0.145 inches and 0.215 inches

**Body Length:** 

Between 0.784 inches and 0.876 inches

**Body Width:** 

Between 0.240 inches and 0.305 inches

**Body Height:** 

0.180 inches

Schematic Diagram Designator:

Isolated array

**Power Dissipation Rating In Watts:** 

1.600 total network

Terminal Width:

Between 0.015 inches and 0.022 inches

**End Application:** 

5805-01-187-9399 telephone switchboard

Identical Value Resistor Quantity:

8 each resistor

Unpackaged Unit Weight:

1.5 grams

Style Designator:

Dual inline

# NSN 5905-01-315-8092

Film Fixed Resistor Network - Page 2 of 2



### **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-r-83401/2 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0