## NSN 5905-01-315-9879

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-315-9879

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0
Electrical Resistance:
4.750 kilohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/ <b>+</b> 125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
10
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
Between 0.125 inches and 0.150 inches
Body Length:
Between 0.968 inches and 0.998 inches
Body Width:
Between 0.177 inches and 0.197 inches
Body Height:
Between 0.050 inches and 0.103 inches
Schematic Diagram Designator:
Isolated array
Power Dissipation Rating In Watts:
0.600 total network
End Application:
5805-01-187-9399 telephone switchboard
Identical Value Resistor Quantity:
5 each resistor
Unpackaged Unit Weight:
1.6 grams
Style Designator:
Single inline
Test Data Document:
81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5905-01-315-9879

Film Fixed Resistor Network - Page 2 of 2



	Sı	peci	fica	tion	Data
--	----	------	------	------	------

81349-mil-r-83401/9 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0