## NSN 5905-01-318-3274

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-318-3274		
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:		
-100.0/+100.0		
Electrical Resistance:		
91.000 kilohms		
Resistance Tolerance In Percent:		
-2.000/+2.000		
Ambient Tempurature In Deg Celsius At Full Rated Power:		
70.0		
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:		
125.0		
Tempurature Range Of Tempurature Coefficient In Deg Celsius:		
-55.0/+125.0		
Inclosure Method:		
Encapsulated		
Terminal Quantity:		
16		
Terminal Type:		
Tab, solder lug		
Reliability Indicator:		
Not established		
Terminal Length:		
Between 0.145 inches and 0.215 inches		
Body Length:		
Between 0.784 inches and 0.876 inches		
Body Width:		
Between 0.240 inches and 0.305 inches		
Body Height:		
0.180 inches		
Schematic Diagram Designator:		
Ladder network		
Power Dissipation Rating In Watts:		
1.500 total network		
Terminal Width:		
Between 0.015 inches and 0.022 inches		
End Application:		
Kok-13/tsec		
Identical Value Resistor Quantity:		
15 each resistor		
Unpackaged Unit Weight:		
1.5 grams		

**Style Designator:**Dual inline

## NSN 5905-01-318-3274

Film Fixed Resistor Network - Page 2 of 2



## **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-83401/2 gov	ernment specification
-------------------------	-----------------------

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_\_

Demilitarization:

No

Fiig:

A001a0