

View Online at <https://aerobasegroup.com/nsn/5905-01-318-3279>

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

Between 0.200 inches and 0.240 inches

Body Length:

Between 0.180 inches and 0.200 inches

Body Width:

Between 0.365 inches and 0.385 inches

Body Height:

Between 0.365 inches and 0.385 inches

Shaft Bearing Type:

Sleeve

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

280.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Maximum Stop Torque:

15.00 inch-ounces

Center To Center Distance Between Terminals:

Between 0.190 inches and 0.210 inches

Fragility Factor:

Moderately rugged

End Application:

Control trmt

Terminal Location:

Rear end

Mounting Method:

Terminal

Features Provided:

Humidity proof

Cubic Measure:

0.027 cubic inches

Electrical Resistance Per Section:

1.0 gallons per minute c and better flooring

Rotary Actuator Travel In Angular Deg:

Between 295.0 and 325.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.185 mils and 0.215 centimeters

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0/+150.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0