## NSN 5905-01-318-4003

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-318-4003				
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:				
-100.0/+100.0				
Electrical Resistance:				
120.000 kilohms				
Resistance Tolerance In Percent:				
-2.000/+2.000				
Ambient Tempurature In Deg Celsius At Full Rated Power:				
70.0				
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:				
125.0				
Tempurature Range Of Tempurature Coefficient In Deg Celsius:				
-55.0/ <b>+</b> 125.0				
Inclosure Method:				
Encapsulated				
Terminal Quantity:				
14				
Terminal Type:				
Tab, solder lug				
Reliability Indicator:				
Not established				
Terminal Length:				
Between 0.125 inches and 0.150 inches				
Body Length:				
Between 0.695 inches and 0.785 inches				
Body Width:				
0.135 inches				
Body Height:				
Between 0.240 inches and 0.305 inches				
Schematic Diagram Designator:				
Isolated array				
Power Dissipation Rating In Watts:				
1.400 total network				
Terminal Width:				
Between 0.015 inches and 0.022 inches				
Identical Value Resistor Quantity:				
7 each resistor				
Unpackaged Unit Weight:				
1.3 grams				
Style Designator:				
Dual inline				
Test Data Document:				

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5905-01-318-4003

Film Fixed Resistor Network - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

81349-mil-r-83401/1 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0