## NSN 5905-01-319-1035

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-319-1035 **Section Quantity: Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.8740 inches and 1.8750 inches Pilot Length: 0.0620 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** Between 0.2494 inches and 0.2497 inches **Shaft Length:** 0.625 inches **Body Length:** 1.020 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 356.0 **Maximum Starting Torque:** 0.80 inch-ounces **Maximum Running Torque:** 0.60 inch-ounces **Shaft End Play:** 0.005 inches

**Shaft Runout:** 0.001 inches

## NSN 5905-01-319-1035

Precision Wire Wound Variable Resistor - Page 2 of 3



Lateral Bound
Lateral Runout:
0.006 inches
Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.002 inches
Mechanical Backlash In Deg Angular Rotation:
1.0
End Application:
Op. Tactics trainer 2ck4-50-4-899
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
1.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
3.5 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Tap Location Tolerance Per Section:
-1.0/+1.0 degrees angular rotation single section
Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-130.0/+130.0 single section
Special Features:
Center tap
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:

-

## NSN 5905-01-319-1035

Precision Wire Wound Variable Resistor - Page 3 of 3



Demilitarization:

No

Fiig:

A002a0