

View Online at <https://aerobasegroup.com/nsn/5905-01-319-4099>

**Section Quantity:**

1

**Body Style:**

Cylindrical

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 0.204 inches and 0.234 inches

**Body Diameter:**

Between 0.770 inches and 0.800 inches

**Body Length:**

Between 0.641 inches and 0.671 inches

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

210.0

**Maximum Starting Torque:**

10.00 inch-ounces

**Maximum Running Torque:**

10.00 inch-ounces

**Center To Center Distance Between Terminals:**

Between 0.423 inches and 0.453 inches

**Fragility Factor:**

Moderately rugged

**End Application:**

6625-00-422-3241 voltmeter, digital

**Terminal Location:**

Front end

**Mounting Method:**

Tab

**Electrical Resistance Per Section:**

1.5 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

240.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

Between 0.204 inches and 0.234 inches

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.25 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0