Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-319-8408

# Section Quantity:

1

Body Style:

Rectangular

## **Reliability Indicator:**

Not established

## Shaft Diameter:

0.061 inches

#### Shaft Length:

3.800 inches

#### **Body Length:**

6.500 inches

### Body Width:

2.700 inches

### **Body Height:**

4.400 inches

## Shaft Style:

Round, slotted

## Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

300.0

### **Fragility Factor:**

Moderately rugged

### **Terminal Location:**

Lower adjacent side single row

### **Mounting Method:**

Clamp ring

### **Features Provided:**

Humidity proof

### **Electrical Resistance Per Section:**

5.0 ohms single section

### **Rotary Actuator Travel In Angular Deg:**

300.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

# Power Dissipation Rating Per Section In Watts:

0.05 free air single section

### **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

### **Actuator Travel Control Feature:**

Clutch



### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0