

View Online at <https://aerobasegroup.com/nsn/5905-01-320-1579>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

1.780 mils and 1.840 centimeters

**Shaft Diameter:**

Between 0.2494 inches and 0.2497 inches

**Shaft Length:**

Between 0.780 inches and 0.840 inches

**Mounting Bushing Length:**

Between 0.280 inches and 0.340 inches

**Body Length:**

Between 1.180 inches and 1.240 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

1080.0

**Maximum Starting Torque:**

1.75 inch-ounces

**Maximum Running Torque:**

1.26 inch-ounces

**Maximum Stop Torque:**

750.00 inch-ounces

**Nonturn Device Location:**

At 12 oclock

**Nonturn Device Radius:**

Between 0.547 inches and 0.577 inches

**Shaft End Play:**

0.010 inches

**Shaft Runout:**

0.002 inches

**Lateral Runout:**

0.005 inches

**Pilot Diameter Runout:**

0.002 inches

**Shaft Radial Play:**

0.003 inches

**Fragility Factor:**

Moderately rugged

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Longitudinally positioned on the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

5.0 percent, rated amperes c and better flooring

**Rotary Actuator Travel In Angular Deg:**

1080.0

**Function Conformity Tolerance Per Section:**

-0.075/+0.075 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Power Dissipation Rating Per Section In Watts:**

3.0 7th secondary quality

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-3.0/+3.0 single section

**Actuator Travel Control Feature:**

Clutch

**Function Characteristic Per Section:**

7 oclock all primaries

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Test Data Document:**

07878-85-32721 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0