

View Online at <https://aerobasegroup.com/nsn/5905-01-320-2491>

Section Quantity:

2

Body Style:

Rectangular

Reliability Indicator:

Not established

Shaft Diameter:

6.0 millimeters

Shaft Length:

Between 19.5 millimeters and 20.5 millimeters

Body Length:

Between 10.8 millimeters and 11.0 millimeters

Body Width:

Between 16.5 millimeters and 17.5 millimeters

Body Height:

Between 18.7 millimeters and 19.7 millimeters

Shaft Style:

Round, milled, spring slit

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 295.0 and 305.0

Maximum Starting Torque:

350.00 centimeter-grams

Maximum Running Torque:

350.00 centimeter-grams

Maximum Stop Torque:

6000.00 centimeter-grams

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 7.1 millimeters and 7.9 millimeters

Shaft End Play:

0.33 millimeters

Fragility Factor:

Moderately rugged

End Application:

Monopole sys

Screw Thread Diameter:

7.0 millimeters

Screw Thread Series Designator:

Iso m

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

20.0 percent, rated amperes c and better finish

Rotary Actuator Travel In Angular Deg:

Between 295.0 and 305.0

Power Dissipation Rating Per Section In Watts:

0.125 free air all sections

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 all sections

Actuator Travel Control Feature:

Stops

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0