NSN 5905-01-320-6865

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-320-6865

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
|---|
| -100.0/+100.0 |
| Electrical Resistance: |
| 2.490 kilohms |
| Resistance Tolerance In Percent: |
| -1.000/+1.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 125.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+125.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Quantity: |
| 16 |
| Terminal Type: |
| Pin |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.125 inches and 0.150 inches |
| Body Length: |
| Between 0.784 inches and 0.876 inches |
| Body Width: |
| Between 0.240 inches and 0.305 inches |
| Body Height: |
| 0.200 inches |
| Schematic Diagram Designator: |
| Isolated array |
| Power Dissipation Rating In Watts: |
| 1.600 total network |
| End Application: |
| Input command |
| Identical Value Resistor Quantity: |
| 8 each resistor |
| Criticality Code Justification: |
| Zzzy |
| Special Features: |
| Item must comply with requirements of defense supply center columbus production standard no. Lo4253 |
| Style Designator: |

Dual inline

NSN 5905-01-320-6865

Film Fixed Resistor Network - Page 2 of 2



Reference Number Differentiating Characteristics:

Breference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp.

| Shelf Life: |
|-------------------|
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A001a0