NSN 5905-01-320-6875

Film Fixed Resistor Network - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5905-01-320-0675 |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -300.0/+300.0 |
| Electrical Resistance: |
| 3.320 kilohms |
| Resistance Tolerance In Percent: |
| -1.000/+1.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 125.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0/+125.0 |
| Inclosure Method: |
| Encapsulated |
| Terminal Quantity: |
| 16 |
| Terminal Type: |
| Tab, solder lug |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| Between 0.105 inches and 0.215 inches |
| Body Length: |
| Between 0.784 inches and 0.876 inches |
| Body Width: |
| Between 0.240 inches and 0.305 inches |
| Body Height: |
| 0.180 inches |
| Schematic Diagram Designator: |
| Ladder network |
| Power Dissipation Rating In Watts: |
| 1.500 total network |
| Terminal Width: |
| Between 0.015 inches and 0.022 inches |
| Identical Value Resistor Quantity: |
| 15 each resistor |
| Style Designator: |
| Dual inline |
| Test Data Document: |
| 81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-83401/2 government specification

NSN 5905-01-320-6875

Film Fixed Resistor Network - Page 2 of 2



| | Life: |
|--|-------|
| | |
| | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0