NSN 5905-01-321-8036

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-321-8036

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-300.0/+300.0
Electrical Resistance:
910.000 ohms
Resistance Tolerance In Percent:
-2.000/+2.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
70.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
16
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
Between 0.105 inches and 0.215 inches
Body Length:
Between 0.784 inches and 0.876 inches
Body Width:
Between 0.240 inches and 0.305 inches
Body Height:
0.180 inches
Schematic Diagram Designator:
Ladder network
Power Dissipation Rating In Watts:
1.500 total network
Terminal Width:
Between 0.015 inches and 0.022 inches
End Application:
Digital comp
Identical Value Resistor Quantity:
15 each resistor
Style Designator:
Dual inline
Test Data Document:
81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5905-01-321-8036

Film Fixed Resistor Network - Page 2 of 2



Spec	ifica	tion	Data:
------	-------	------	-------

81349-mil-r-83401/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0