NSN 5905-01-322-1584

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-322-1584

103.000 ohms Resistance Tolerance in Percent: -2.000/4-2.000 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: -70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: -70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: -70.0 Inclosure Method: Uninclosed Terminal Type: -70.0 Terminal Type probdy style Reliability Tellure Rate Level in Percent: -70.0 Body Length: -70.0 0.010 Body Length: -70.0 0.050 inches -70.0 Body Height: -70.0 Body Height: -70.0 Between 0.010 inches and 0.040 inches -70.0 Body Height: -70.0 Between 0.010 inches and 0.040 inches -70.0 Between 0.010 inches and 0.040 inches -70.0 Body Height: -70.0 Between 0.010 inches and 0.040 inches -70.0 Between 0.010 inches -70.0 Between	Electrical Resistance:
Resistance Tolerance in Percent: -2.0004-2.0000 Ambient Tempurature in Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclossed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Bedy Length: 0.150 inches Body Unith: 0.050 inches Body Width: 0.050 inches Body Height: Bettween 0.010 inches and 0.040 inches Power Dissipation Rating in Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: 81349-mill-F55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mill-F55342/4 government specification Specification Space Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.150 Inches Body Width: 0.050 Inches Body Width: 0.050 Inches Body Height: Between 0.010 Inches and 0.040 Inches Power Dissipation Rating In Watts: 0.150 Iree air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.150 inches Body Length: 0.150 inches Body Width: 0.050 inches Body Width: 0.050 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: 81349-mil+75542 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil+755342 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.050 inches Body Width: 0.050 inches Body Width: 0.050 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Terminalton pad each end Test Data Document: B1349-mili-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mili-53342 government specification Sheff Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Inclosure Method: Uninclosed Terminal Type: Terminal Type: Terminal Type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.150 inches Body Width: 0.050 inches Body Width: 0.050 inches Body Height: Battween 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Terminalton pad each end Terminalton pad each end Termination pad each end Termination pad each end Termination pad each end end Termination pad each end end: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-553424 government specification Shelf Life: N/a Unit Of Measure:	
Inclosure Method: Uninclosed Terminal Type: Terminal Type per body style Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Body Length: 0.150 inches Body Width: 0.050 inches Body Width: 0.050 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating in Watts: 0.150 free air Style Designator: Termination pad each end Tests Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure:	
Inciosure Method: Uninciosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Body Length: 0.0150 inches Body Width: 0.050 inches Body Width: 0.050 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating in Watts: 0.150 rea in: Style Designator: Termination pad each end Test Data Document: 81349-milr-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-milr-55342/4 government specification Shelf Life: N/a Unit Of Measure:	
Uninclosed Terminal Type: Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.150 inches Body Width: 0.050 inches Body Width: 0.050 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: Style Designator: Style Designator: Termination pad each end Test Data Document: Ba1349-milr-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-milr-55342/4 government specification Sheft Life: N/a Unit Of Measure: Demiliterization: No Filg:	
Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level in Percent: 0.010 Body Length: 0.150 inches Body Width: 0.050 inches Body Width: 0.050 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: 181349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-553424 government specification Sheft Life: N/a Unit Of Measure: Demilitarization: No Filig:	
Terminal type per body style Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.050 Inches Body Width: 0.050 Inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similiar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.150 inches Body Width: 0.050 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure:	
Established Reliability Failure Rate Level In Percent: 0.010 Body Length: 0.150 inches Body Width: 0.050 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating in Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Body Length: 0.150 inches Body Width: 0.050 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: B1349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure:	
Body Length: 0.150 inches Body Width: 0.050 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: B1349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: B1349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure:	Reliability Failure Rate Level In Percent:
0.150 inches Body Width: 0.050 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	•
Body Width: 0.050 inches Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
Body Height: Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.150 inches
Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	Body Width:
Between 0.010 inches and 0.040 inches Power Dissipation Rating In Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.050 inches
Power Dissipation Rating In Watts: 0.150 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Height:
O.150 free air Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.010 inches and 0.040 inches
Style Designator: Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fitig:	Power Dissipation Rating In Watts:
Termination pad each end Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.150 free air
Test Data Document: 81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Termination pad each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-55342 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Specification Data: 81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-mil-r-55342/4 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Specification Data:
N/a Unit Of Measure: Demilitarization: No Fiig:	81349-mil-r-55342/4 government specification
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0