

View Online at <https://aerobasegroup.com/nsn/5905-01-322-9458>

Section Quantity:

1

Body Style:

Cylindrical, edge control operated

Reliability Indicator:

Not established

First Flat Length:

1.562 inches

Flat Height:

0.344 inches

Body Diameter:

8.000 inches

Shaft Diameter:

0.375 inches

Shaft Length:

2.000 inches

Body Length:

2.125 inches

Shaft Style:

Round, flatted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

325.0

Maximum Starting Torque:

7.00 inch-ounces

Maximum Running Torque:

7.00 inch-ounces

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unc

Screw Thread Qty Per Inch (tpi):

20.0

Mounting Facility Quantity:

2

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Threaded hole

Features Provided:

Humidity proof

Electrical Resistance Per Section:

5.0 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

325.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

500.0 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0