

View Online at <https://aerobasegroup.com/nsn/5905-01-324-7115>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

1.094 inches

Shaft Diameter:

Between 0.248 inches and 0.251 inches

Shaft Length:

Between 0.844 inches and 0.906 inches

Mounting Bushing Length:

Between 0.342 inches and 0.432 inches

Body Length:

Between 0.719 inches and 0.969 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Switch Type:

Rotary

Switch Voltage Rating In Volts:

117.0

Contact Arm Electrical Off Position:

Fully ccw

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 330.0 and 340.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Maximum Stop Torque:

128.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.515 inches and 0.547 inches

Switch Operating Position:

Start of rotation

Switch Contact Arrangement:

Single pole, single throw, normally open, both positions maintained

Fragility Factor:

Moderately rugged

End Application:

5895-01-138-5644 sensor monitori

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof and panel seal and shaft seal and switch

Cubic Measure:

0.778 cubic inches

Electrical Resistance Per Section:

75.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 330.0 and 340.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Switch Current Type And Rating In Amps:

3.000 ac

Standard Taper Curve Per Section:

A single section

Test Data Document:

81349-mil-r-94 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0