## NSN 5905-01-325-3837

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-325-3837

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.9688 inches
Pilot Length:
0.0620 inches
Undercut Diameter:
0.937 inches
Undercut Width:
0.0620 inches
Body Diameter:
1.062 inches
Shaft Diameter:
0.124 inches
Shaft Length:
0.875 inches
Body Length:
0.681 inches
Mounting Lip Diameter:
1.0620 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.000 kilohms single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
1.5 free air single section
Resistance Tolerance Per Section In Percent:
3.0/13.0 single section

-3.0/+3.0 single section

## NSN 5905-01-325-3837

Precision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature Ir	n Deg Celsius	Per Section A	t Full Rated Power:
------------------------	---------------	---------------	---------------------

65.0 single section

**Terminal Type And Quantity:** 

3 turret

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0