NSN 5905-01-325-5209

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-325-5209 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.750 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 248.0 **Fragility Factor:** Moderately rugged **End Application:** Test set **Terminal Location:** Rear end **Mounting Method:** Tab **Electrical Resistance Per Section:** 1.5 kilohms single section **Rotary Actuator Travel In Angular Deg:** 250.0 **Power Dissipation Rating Per Section In Watts:** 3.0 free air single section **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section **Actuator Travel Control Feature:** Stops Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 40.0 single section **Standard Taper Curve Per Section:** A single section **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5905-01-325-5209

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Fiig:

A002a0