NSN 5905-01-325-8834

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-325-8834
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0
Electrical Resistance:
4.020 kilohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
14
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
Between 0.105 inches and 0.215 inches
Body Length:
Between 0.695 inches and 0.785 inches
Body Width:
Between 0.240 inches and 0.305 inches
Body Height:
0.180 inches
Schematic Diagram Designator:
Isolated array
Power Dissipation Rating In Watts:
1.400 total network
Terminal Width:
Between 0.015 inches and 0.022 inches
Identical Value Resistor Quantity:
7 each resistor
Style Designator:
Dual inline
Test Data Document:
81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-83401/1 government specification

NSN 5905-01-325-8834

Film Fixed Resistor Network - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0