NSN 5905-01-325-8837

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-325-8837			
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:			
-100.0/+100.0			
Electrical Resistance:			
100.000 kilohms			
Resistance Tolerance In Percent:			
-1.000/+1.000			
Ambient Tempurature In Deg Celsius At Full Rated Power:			
70.0			
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:			
125.0			
Tempurature Range Of Tempurature Coefficient In Deg Celsius:			
-55.0/ + 125.0			
Inclosure Method:			
Encapsulated			
Terminal Quantity:			
14			
Terminal Type:			
Tab, solder lug			
Reliability Indicator:			
Not established			
Terminal Length:			
Between 0.105 inches and 0.215 inches			
Body Length:			
Between 0.695 inches and 0.785 inches			
Body Width:			
Between 0.240 inches and 0.305 inches			
Body Height:			
0.180 inches			
Schematic Diagram Designator:			
Ladder network			
Power Dissipation Rating In Watts:			
1.300 total network			
Terminal Width:			
Between 0.015 inches and 0.022 inches			
End Application:			
Idp cat iii			
Identical Value Resistor Quantity:			
13 each resistor			
Style Designator:			
Dual inline			
Test Data Document:			

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5905-01-325-8837

Film Fixed Resistor Network - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

81349-mil-r-83401/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0