NSN 5905-01-325-9362

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-325-9362 **Section Quantity:** 1 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.875 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** Between 0.563 inches and 0.625 inches **Body Width:** Between 0.609 inches and 0.641 inches **Body Height:** Between 0.609 inches and 0.641 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Maximum Stop Torque:** 64.00 inch-ounces **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.531 inches

Fragility Factor: Moderately rugged **End Application:** Power supply **Screw Thread Diameter:** 0.375 inches

NSN 5905-01-325-9362

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Ferminal Location:
Lower adjacent side two rows
Mounting Method:
Standard bushing
Features Provided:
Humidity proof
Cubic Measure:
0.257 cubic inches
Electrical Resistance Per Section:
.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Resistance Tempurature Characteristic Range Per Section In Percent:
5.0/+5.0 -55 degrees celsius single section and -3.0/+3.0 -25 degrees celsius single section and -1.5/+1.5 0 degrees celsius single section
and -3.0/+3.0 85 degrees celsius single section and -5.0/+5.0 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
50.0 single section
Fempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Resistance Tolerance Per Section In Percent:
5.0/+5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Ferminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Filg: