NSN 5905-01-326-7820

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-326-7820

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:				
-100.0/+100.0				
Electrical Resistance:				
220.000 ohms				
Resistance Tolerance In Percent:				
-2.000/+2.000				
Ambient Tempurature In Deg Celsius At Full Rated Power:				
70.0				
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:				
125.0				
Tempurature Range Of Tempurature Coefficient In Deg Celsius:				
-55.0/+125.0				
Inclosure Method:				
Encapsulated				
Terminal Quantity:				
14				
Terminal Type:				
Tab, solder lug				
Reliability Indicator:				
Not established				
Terminal Length:				
Between 0.105 inches and 0.215 inches				
Body Length:				
Between 0.695 inches and 0.785 inches				
Body Width:				
Between 0.240 inches and 0.305 inches				
Body Height:				
0.180 inches				
Schematic Diagram Designator:				
Ladder network				
Power Dissipation Rating In Watts:				
1.200 total network				
Terminal Width:				
Between 0.015 inches and 0.022 inches				
Identical Value Resistor Quantity:				
12 lowest resistance value				
Style Designator:				
Dual inline				
Test Data Document:				
81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification				
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain				

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-r-83401/1 government specification

NSN 5905-01-326-7820

Film Fixed Resistor Network - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0