## NSN 5905-01-327-0906

**Section Quantity:** 

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-327-0906

oodion quantity.
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Terminal Length:
Between 0.531 inches and 0.563 inches
First Flat Length:
Between 0.234 inches and 0.266 inches
Flat Height:
Between 0.092 inches and 0.096 inches
Body Diameter:
Between 0.484 inches and 0.516 inches
Shaft Diameter:
Between 0.124 inches and 0.126 inches
Shaft Length:
Between 1.859 inches and 1.891 inches
Mounting Bushing Length:
Between 0.234 inches and 0.266 inches
Body Length:
0.500 inches
Shaft Style:
Round, flatted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
270.0
Maximum Starting Torque:
3.00 inch-ounces
Maximum Running Torque:
3.00 inch-ounces
Maximum Stop Torque:
64.00 inch-ounces
Nonturn Device Location:
At 10'30 oclock
Nonturn Device Radius:
Between 0.240 inches and 0.250 inches
Mechanical Backlash In Deg Angular Rotation:
3.0

## NSN 5905-01-327-0906

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Terminals:
0.200 inches
Fragility Factor:
Moderately rugged
End Application:
Digital multi
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 290.0 and 300.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A002a0