

View Online at <https://aerobasegroup.com/nsn/5905-01-327-6408>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

First Flat Length:

0.375 inches

Flat Height:

0.215 inches

Body Diameter:

1.560 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.465 inches

Mounting Bushing Length:

1.012 inches

Body Length:

1.230 inches

Shaft Style:

Round, flatted

Shaft Bearing Type:

Bearing

Contact Arm Electrical Off Position:

Fully ccw-cw

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

335.0

Nonturn Device Location:

At 5: 00 oclock and at 7 oclock

Nonturn Device Radius:

0.210 inches

Screw Thread Diameter:

0.368 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Locking bushing

Electrical Resistance Per Section:

3.0 ohms single section

Rotary Actuator Travel In Angular Deg:

338.0

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

25.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0