## NSN 5905-01-328-3788

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-328-3788		
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:		
-30.0/+30.0		
Electrical Resistance:		
105.000 ohms		
Resistance Tolerance In Percent:		
-1.000/+1.000		
Ambient Tempurature In Deg Celsius At Full Rated Power:		
25.0		
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:		
275.0		
Tempurature Range Of Tempurature Coefficient In Deg Celsius:		
-55.0/+275.0		
Inclosure Method:		
Encased		
Terminal Type:		
Tab, solder lug		
Reliability Indicator:		
Established		
Reliability Failure Rate Level In Percent:		
0.010		
Terminal Length:		
Between 0.376 inches and 0.500 inches		
Body Length:		
Between 1.876 inches and 2.000 inches		
Body Width:		
Between 0.532 inches and 0.656 inches		
Body Height:		
Between 0.594 inches and 0.656 inches		
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:		
Between 1.552 inches and 1.572 inches		
Power Dissipation Rating In Watts:		
10.000 free air		
Terminal Width:		
0.140 inches		
End Application:		
Dpm 22 7m upg		
Mounting Hole Size:		
Between 0.120 inches and 0.130 inches		
Cubic Measure (non-core):		

0.719 cubic inches

**Unpackaged Unit Weight:** 

32.0 grams

## NSN 5905-01-328-3788

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Style	Desia	nator:

Axial terminal (s)

## **Test Data Document:**

81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-39009/1 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0