NSN 5905-01-328-8921

Film Fixed Resistor - Page 1 of 2



view Online at https://aerobasegroup.com/hsn/5905-01-326-6921
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0 to 100.0
Electrical Resistance:
422.000 ohms
Resistance Tolerance In Percent:
-1.000 to 1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0 to 125.0
Inclosure Method:
Uninclosed
Terminal Type:
Terminal type per body style
Reliability Indicator:
Not established
Body Length:
Between 0.055 inches and 0.069 inches
Body Width:
Between 0.118 inches and 0.134 inches
Body Height:
Between 0.016 inches and 0.028 inches
Power Dissipation Rating In Watts:
0.125 free air
End Application:
Los angeles class ssn (688), kidd class ddg, forrestal class cv, nimitz class cvn, spruance class dd (963), arleigh burke class ddg,
ticonderoga class cg (47), oliver perry class ffg. Landing craft air cushion (lcac).
Criticality Code Justification:
Feat
Special Features:
Weapon system essential
Precious Material And Location:
Terminal surfaces palladium and terminal surfaces silver
Style Designator:
Termination pad each end
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

NSN 5905-01-328-8921

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0