NSN 5905-01-328-8926

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-328-8926

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0 to 100.0

Electrical Resistance:

383.000 ohms

Resistance Tolerance In Percent:

-1.000 to 1.000

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 125.0

Inclosure Method:

Uninclosed

Terminal Type:

Terminal type per body style

Reliability Indicator:

Not established

Body Length:

Between 0.055 inches and 0.069 inches

Body Width:

Between 0.118 inches and 0.134 inches

Body Height:

Between 0.016 inches and 0.028 inches

Power Dissipation Rating In Watts:

0.125 free air

End Application:

Forrestal class cv, nimitz class cvn, landing craft air cushion (lcac), arleigh burke class ddg, ticonderoga class cg (47), spruance class dd (963), kidd class ddg, los angeles class ssn (688), oliver perry class ffg.

Criticality Code Justification:

Feat

Special Features:

Weapon system essential

Precious Material And Location:

Terminal surfaces palladium and terminal surfaces silver

Style Designator:

Termination pad each end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5905-01-328-8926

Film Fixed Resistor - Page 2 of 2

Fiig: A001a0

