# NSN 5905-01-329-1070

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-329-1070

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0 to 100.0

### **Electrical Resistance:**

237.000 ohms

## **Resistance Tolerance In Percent:**

-1.000 to 1.000

### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 125.0

### **Inclosure Method:**

Uninclosed

## Terminal Type:

Terminal type per body style

## **Reliability Indicator:**

Not established

### **Body Length:**

Between 0.055 inches and 0.069 inches

### **Body Width:**

Between 0.118 inches and 0.134 inches

### **Body Height:**

Between 0.016 inches and 0.028 inches

### **Power Dissipation Rating In Watts:**

0.125 free air

### **End Application:**

Ticonderoga class cg (47), forrestal class cv, nimitz class cvn, spruance class dd (963), austin ship class ldp-4 amphibious transport docks, arleigh burke class ddg, kidd class ddg, los angeles class ssn (688), oliver perry class ffg, seawolf class ssn.

## Criticality Code Justification:

Feat

### **Special Features:**

Weapon system essential

### **Precious Material And Location:**

Terminal surfaces palladium and terminal surfaces silver

#### Style Designator:

Termination pad each end

### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5905-01-329-1070

Film Fixed Resistor - Page 2 of 2

**Fiig:** A001a0

