## NSN 5905-01-329-1072

Film Fixed Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-329-1072  |
|--|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:  |
| -100.0 to 100.0  |
| Electrical Resistance:   |
| 46.400 ohms  |
| Resistance Tolerance In Percent:   |
| -1.000 to 1.000  |
| Ambient Tempurature In Deg Celsius At Full Rated Power:  |
| 70.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  |
| 125.0  |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:   |
| -55.0 to 125.0   |
| Inclosure Method:  |
| Uninclosed   |
| Terminal Type:   |
| Terminal type per body style   |
| Reliability Indicator:   |
| Not established  |
| Body Length:   |
| Between 0.055 inches and 0.069 inches  |
| Body Width:  |
| Between 0.118 inches and 0.134 inches  |
| Body Height:   |
| Between 0.016 inches and 0.028 inches  |
| Power Dissipation Rating In Watts:   |
| 0.125 free air   |
| End Application:   |
| Landing craft air cushion (lcac). Forrestal class cv, arleigh burke class ddg, spruance class dd (963), kidd class ddg, oliver perry class ffg |
| nimitz class cvn, los angeles class ssn (688), ticonderoga class cg (47).  |
| Criticality Code Justification:  |
| Feat   |
| Special Features:  |
| Weapon system essential  |
| Precious Material And Location:  |
| Terminal surfaces palladium and terminal surfaces silver   |
| Style Designator:  |
| Termination pad each end   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |

No

Demilitarization:

## NSN 5905-01-329-1072

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0