NSN 5905-01-329-4925

Film Fixed Resistor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-329-4925 |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -100.0 to 100.0 |
| Electrical Resistance: |
| 681.000 ohms |
| Resistance Tolerance In Percent: |
| -1.000 to 1.000 |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 125.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0 to 125.0 |
| Inclosure Method: |
| Uninclosed |
| Terminal Type: |
| Terminal type per body style |
| Reliability Indicator: |
| Not established |
| Body Length: |
| Between 0.055 inches and 0.069 inches |
| Body Width: |
| Between 0.118 inches and 0.134 inches |
| Body Height: |
| Between 0.016 inches and 0.028 inches |
| Power Dissipation Rating In Watts: |
| 0.125 free air |
| End Application: |
| Kidd class ddg, oliver perry class ffg, iiconderoga class cg (47), landing craft air cushion (lcac), spruance class dd (963), arleigh burke |
| class ddg, los angeles class (688), forrestal class cv, nimitz class cvn |
| Criticality Code Justification: |
| Feat |
| Special Features: |
| Weapon system essential |
| Precious Material And Location: |
| Terminal surfaces palladium and terminal surfaces silver |
| Style Designator: |
| Termination pad each end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

No

Demilitarization:

NSN 5905-01-329-4925

Film Fixed Resistor - Page 2 of 2



Fiig:

A001a0