Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-329-9437

Section	Quantity:
1	

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Terminal Length:

0.125 inches

Body Diameter:

0.480 mils and 0.520 centimeters

Shaft Diameter:

0.125 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.250 inches

Body Length:

Between 0.468 inches and 0.500 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 290.0 and 300.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Maximum Stop Torque:

48.00 inch-ounces

Nonturn Device Location:

At 4'30 oclock and at 10'30 oclock

Nonturn Device Radius:

Between 0.229 inches and 0.250 inches

Center To Center Distance Between Terminals:

Between 0.195 inches and 0.205 inches

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.250 inches

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Screw Thread Series Designator: Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Center To Center Distance Between Terminal Rows:

Between 0.195 inches and 0.205 inches

Features Provided:

Humidity proof and shaft seal

Cubic Measure:

0.095 cubic inches

Electrical Resistance Per Section:

10.0 percent, rated amperes c and better flooring

Rotary Actuator Travel In Angular Deg:

Between 290.0 and 300.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Resistance Tempurature Characteristic Range Per Section In Percent:

+0.0/+7.0 -55 degrees celsius single section and +0.0/+5.5 -40 degrees celsius single section and +0.0/+2.0 0 degrees celsius single section

and -2.5/+2.5 85 degrees celsius single section and -5.5/+5.5 -25 degrees celsius single section

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 7th secondary quality

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0