# NSN 5905-01-332-2561

Film Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-332-2561

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-5.0/+5.0 first temp coefficient

# **Electrical Resistance:**

3.440 kilohms

# **Resistance Tolerance In Percent:**

-0.100/+0.100

# Ambient Tempurature In Deg Celsius At Full Rated Power:

# 125.0

# Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

175.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0 temp range of first temp coefficient

#### **Inclosure Method:**

Encapsulated

### **Terminal Type:**

Wire lead

## Mil-std-1276 Wire Lead Type Designator:

С

### **Reliability Indicator:**

Established

# Reliability Failure Rate Level In Percent:

0.010

### **Terminal Length:**

Between 0.875 inches and 1.875 inches

### **Body Length:**

Between 0.290 inches and 0.320 inches

### Body Width:

0.336 inches

**Body Height:** 

Between 0.095 inches and 0.120 inches

### Power Dissipation Rating In Watts:

0.300 free air

End Application:

An/tyq-2 (v) 1

Cubic Measure (non-core):

0.013 cubic inches

Unpackaged Unit Weight:

1.0 grams

Style Designator:

Terminals one edge

### **Test Data Document:**

81349-mil-r-55182 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5905-01-332-2561

Film Fixed Resistor - Page 2 of 2



**Specification Data:** 

81349-mil-r-55182/9 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0