Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-332-5609

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-300.0/+300.0

#### **Electrical Resistance:**

150.000 kilohms

# **Resistance Tolerance In Percent:**

-2.000/+2.000

#### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Quantity:**

8

## Terminal Type:

Pin

# **Reliability Indicator:**

Not established

# Terminal Length:

Between 0.125 inches and 0.150 inches

## **Body Length:**

Between 0.768 inches and 0.798 inches

## **Body Width:**

Between 0.050 inches and 0.103 inches

## **Body Height:**

Between 0.177 inches and 0.197 inches

## Schematic Diagram Designator:

Ladder network

## **Power Dissipation Rating In Watts:**

0.840 total network

#### **End Application:**

An/tyq-2 (v) 1

## Identical Value Resistor Quantity:

7 each resistor

#### Style Designator:

Single inline

## **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-r-83401/8 government specification

# NSN 5905-01-332-5609

Film Fixed Resistor Network - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0

