## NSN 5905-01-332-9246

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-332-9246

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+100.0
Electrical Resistance:
1.000 kilohms
Resistance Tolerance In Percent:
-2.000/+2.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+125.0
Inclosure Method:
Encapsulated
Terminal Quantity:
16
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
Terminal Length: 0.036 inches
0.036 inches
0.036 inches  Body Length:
0.036 inches  Body Length:  Between 0.430 inches and 0.450 inches
0.036 inches  Body Length:  Between 0.430 inches and 0.450 inches  Body Width:
0.036 inches  Body Length:  Between 0.430 inches and 0.450 inches  Body Width:  Between 0.215 inches and 0.225 inches
0.036 inches  Body Length:  Between 0.430 inches and 0.450 inches  Body Width:  Between 0.215 inches and 0.225 inches  Body Height:
0.036 inches  Body Length:  Between 0.430 inches and 0.450 inches  Body Width:  Between 0.215 inches and 0.225 inches  Body Height:  Between 0.075 inches and 0.085 inches
0.036 inches  Body Length:  Between 0.430 inches and 0.450 inches  Body Width:  Between 0.215 inches and 0.225 inches  Body Height:  Between 0.075 inches and 0.085 inches  Schematic Diagram Designator:
0.036 inches  Body Length:  Between 0.430 inches and 0.450 inches  Body Width:  Between 0.215 inches and 0.225 inches  Body Height:  Between 0.075 inches and 0.085 inches  Schematic Diagram Designator:  Isolated array
0.036 inches  Body Length: Between 0.430 inches and 0.450 inches  Body Width: Between 0.215 inches and 0.225 inches  Body Height: Between 0.075 inches and 0.085 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts:
0.036 inches  Body Length: Between 0.430 inches and 0.450 inches  Body Width: Between 0.215 inches and 0.225 inches  Body Height: Between 0.075 inches and 0.085 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts:  0.250 total network
0.036 inches  Body Length:  Between 0.430 inches and 0.450 inches  Body Width:  Between 0.215 inches and 0.225 inches  Body Height:  Between 0.075 inches and 0.085 inches  Schematic Diagram Designator:  Isolated array  Power Dissipation Rating In Watts:  0.250 total network  Terminal Width:
0.036 inches  Body Length: Between 0.430 inches and 0.450 inches  Body Width: Between 0.215 inches and 0.225 inches  Body Height: Between 0.075 inches and 0.085 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts: 0.250 total network  Terminal Width: 0.018 inches
Body Length: Between 0.430 inches and 0.450 inches Body Width: Between 0.215 inches and 0.225 inches Body Height: Between 0.075 inches and 0.085 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.250 total network Terminal Width: 0.018 inches End Application:
0.036 inches  Body Length: Between 0.430 inches and 0.450 inches  Body Width: Between 0.215 inches and 0.225 inches  Body Height: Between 0.075 inches and 0.085 inches  Schematic Diagram Designator: Isolated array  Power Dissipation Rating In Watts: 0.250 total network  Terminal Width: 0.018 inches  End Application: Intercom set
Body Length: Between 0.430 inches and 0.450 inches Body Width: Between 0.215 inches and 0.225 inches Body Height: Between 0.075 inches and 0.085 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.250 total network Terminal Width: 0.018 inches End Application: Intercom set Identical Value Resistor Quantity:
Body Length: Between 0.430 inches and 0.450 inches Body Width: Between 0.215 inches and 0.225 inches Body Height: Between 0.075 inches and 0.085 inches Schematic Diagram Designator: Isolated array Power Dissipation Rating In Watts: 0.250 total network Terminal Width: 0.018 inches End Application: Intercom set Identical Value Resistor Quantity: 8 each resistor

N/a

## NSN 5905-01-332-9246

Film Fixed Resistor Network - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A001a0