NSN 5905-01-333-7640

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-333-7640 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Terminal Length:** 6.35 millimeters **Body Diameter:** 6.5 major centimeters **Shaft Diameter:** 2.9 millimeters **Shaft Length:** 1.0 millimeters **Body Length:** 5.3 millimeters **Shaft Style:** Round, slotted **Shaft Bearing Type:** Bearing **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 190.0 and 240.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Center To Center Distance Between Terminals:** 5.08 millimeters **Fragility Factor:** Moderately rugged **End Application:** 5865-01-188-3309 jammer system, r **Terminal Location:** Rear end

Mounting Method:
Terminal
Features Provided:
Humidity proof
Cubic Measure:
0.011 cubic inches

NSN 5905-01-333-7640

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
200.0 ohms c and better flooring
Rotary Actuator Travel In Angular Deg:
Between 240.0 and 300.0
Center To Center Distance Between Center Terminal And Outside Terminal:
2.54 major inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 7th secondary quality
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Δ002a0