NSN 5905-01-336-1252

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-336-1252 **Section Quantity: Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Terminal Length:** 0.203 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.594 inches **Body Width:**

0.625 inches **Body Height:** 0.625 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Center To Center Distance Between Terminals:** 0.100 inches **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side two rows **Mounting Method:** Standard bushing

NSN 5905-01-336-1252

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Terminal Rows:
0.203 inches
Electrical Resistance Per Section:
100.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Terminal Type And Quantity:
2 pin and 1 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: