

View Online at <https://aerobasegroup.com/nsn/5905-01-337-0280>

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

0.200 inches

Body Length:

0.190 inches

Body Width:

Between 0.365 inches and 0.385 inches

Body Height:

Between 0.365 inches and 0.385 inches

Shaft Bearing Type:

Bearing

Actuator Type:

Recessed drive with slot

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

0.300 inches

Fragility Factor:

Moderately rugged

End Application:

6625-01-196-8335 test set, electr

Terminal Location:

Lower adjacent side single row

Mounting Method:

Terminal

Features Provided:

Humidity proof

Cubic Measure:

0.028 cubic inches

Electrical Resistance Per Section:

500.0 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

0.150 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0/+100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0