## NSN 5905-01-338-1928

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-338-1928

| Townwature Coefficient Of Resistance In Dum Der Der Coleius     |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
| -100.0/+100.0   |
| Electrical Resistance:  |
| 1.000 kilohms   |
| Resistance Tolerance In Percent:                                |
| -2.000/+2.000   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:         |
| 70.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 125.0   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:    |
| -55.0/+125.0  |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Quantity:  |
| 8   |
| Terminal Type:  |
| Pin   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| Between 0.146 inches and 0.171 inches                           |
| Body Length:  |
| Between 0.768 inches and 0.798 inches                           |
| Body Width:   |
| Between 0.050 inches and 0.103 inches                           |
| Body Height:  |
| Between 0.332 inches and 0.350 inches                           |
| Schematic Diagram Designator:                                   |
| Ladder network  |
| Power Dissipation Rating In Watts:                              |
| 1.400 total network   |
| End Application:  |
| Lan target po   |
| Identical Value Resistor Quantity:                              |
| 7 each resistor   |
| Style Designator:   |
| Single inline   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 5905-01-338-1928

Film Fixed Resistor Network - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0