NSN 5905-01-338-3468

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-338-3468

Section Quantity
Section Quantity:
Body Style:
Rectangular Poliability Indicators
Reliability Indicator:
Not established
Shaft Diameter: 0.150 inches
Shaft Length: 0.080 inches
Body Length:
Between 0.354 inches and 0.394 inches
Body Width:
0.150 inches
Body Height:
Between 0.354 inches and 0.394 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Maximum Starting Torque:
5.00 inch-ounces
Maximum Running Torque:
5.00 inch-ounces
Fragility Factor:
Moderately rugged
End Application:
Alarm set ant
Terminal Location:
Left adjacent side two rows
Mounting Method:
Terminal
Features Provided:
Humidity proof
Electrical Resistance Per Section:
20.0 percent, rated amperes c and better flooring
Rotary Actuator Travel In Angular Deg:

360.0

NSN 5905-01-338-3468

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 150.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 7th secondary quality **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Clutch Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** Immersion sealed **Terminal Type And Quantity:** 3 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No