NSN 5905-01-338-5488

No

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-338-5488

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0/+500.0
Electrical Resistance:
0.510 ohms
Resistance Tolerance In Percent:
-10.000/+10.000 Ambient Tempurature In Dea Coleius At Full Beted Bowers
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0/+350.0
Inclosure Method:
Encapsulated To the state of th
Terminal Type:
Tab, solder lug
Reliability Indicator:
Not established
Terminal Length:
0.563 inches
Body Diameter:
1.312 inches
Body Length:
Between 10.438 inches and 10.562 inches
Power Dissipation Rating In Watts:
210.000 free air
Terminal Width:
Between 0.172 inches and 0.328 inches
End Application:
Minuteman Is
Style Designator:
Radial terminal each end
Test Data Document:
81349-mil-r-26 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-26/3 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

NSN 5905-01-338-5488

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0